



AX-514

Half Size Convection Oven Manual controls - 4 shelves







Manual controls	Time, temperature
Load capacity	4 shelves for half size sheet pans
Fan	1 (2200 rpm)
Space between shelves	3" (75 mm)
Power requirements	2,700 Watts / 208-240 V / 60 / 1
	Oven supplied with power cord and plug
Temperature	86° - 540° F
Equipped with	120 minute timer - Signal at end of cycle
Cavity size (inches)	18.7" x 15.9" x 12.6" (WxDxH)
Unit dimensions (inches)	22.05" x 25.48" x 20.85" (WxDxH)
Shipping dimensions	23.63" x 26.77" x 21.65" (WxDxH)
(inches)	
Net / Ship weight	69 lb / 75 lb

Features

- Advanced airflow design
- Manual control: 120 minute timer or continuous ON
- Interior halogen light
- Heavy duty stainless steel body construction
- "Cold Door" design with double pane glass
- Reinforced door hinges
- Oven door can support weight limit of 60 lbs.
- Oven cavity is insulated with ultra-high temperature fiberglass insulation
- 4 Stainless steel wire shelves
- Ovens can be staked (kit required)
- Warranty: 2 years parts & 1 year labor exclusive of lights, gaskets and glass

OVEN STANDS & PROOFERS



AX-501 OVEN STAND SHIP WT: 43 lbs

- HD stand with tray slides for half size sheet pans
- Dimensions: 23.30" x 20.87" x 31.50"
- Accommodates any "5" series ovens



AX-PR5 SHIP WT: 133 lbs



- Capacity: 8 half size sheet pans
- Space between pans: 3"
- 208-240/60/1, 2000 Watts
- Heat setting up to 140°F
- Manual fill water supply in bottom tray

CONVECTION ACCESSORIES



DEFLECTOR CODE: **124-DEF**

- 1 is required for "5" series
- Air deflector plate for delicate baking



STACKING KIT "5" SERIES CODE: 124-KIT5

- Stacking kit for "5" Series

LINE DRAWINGS

AX-514



